

512, 132  
10/512132

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number  
WO 03/091866 A1

(51) International Patent Classification<sup>7</sup>: G06F 3/023, H04M 1/247

(21) International Application Number: PCT/GB02/01878

(22) International Filing Date: 26 April 2002 (26.04.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HANNAY, Alexander [GB/GB]; 3 The Orchard,, London W4 1JZ (GB).

(74) Agents: HIGGIN, Paul et al.; Swindell & Pearson, 48 Friar Gate, Derby DE1 1GY (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: USER INTERFACE



(57) Abstract: A user input device for providing 8-way directional control, comprising a first set of sensors consisting of a first sensor (131) adjacent a second sensor (132), constituting a first pair of sensors, and a third sensor (133) adjacent the second sensor (132), constituting a second pair of sensors; and a second set of sensors, adjacent the second set of sensors, consisting of a fourth sensor (134) adjacent a fifth sensor (135), constituting a third pair of sensors, and a sixth sensor (136) adjacent the fifth sensor (135), constituting a fourth pair of sensors; wherein user actuation of a respective one of at least four of the six sensors provides for control in a respective one of four different directions and user actuation of a respective one of the first, second, third and fourth pairs of sensors provides for control in a respective one of the remaining four different directions.

WO 03/091866 A1

WO 03/091866 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

### User Interface

The present invention relates to a user interface for a hand portable device. In particular, it relates to a input mechanism using the keypad of the hand portable device.

At the present time, desktop computers use peripheral devices for user input. The mouse is the standard cursor control device used for most applications. The joystick is the standard input device used for gaming. Both of these devices are relatively bulky and are connected to the desktop computer. They are therefore generally unsuitable for portable computing. In one type of portable computer, the keyboard has integrated within it a joystick-like device which can be used to control the cursor instead of a mouse.

It would be desirable to provide joystick-like control in a hand portable device without having to integrate a joystick or use peripheral devices.

One way of providing joystick like control on a mobile phone would be to assign a key in a numeric keypad to each of 8 directional movements: North, South, East, West, North-East, South-East, South-West and North West. Thus the keypad would be operable as an 8-way directional controller. This would be achieved using the array of three columns and four rows of data input keys on a mobile phone by assigning three of the rows to 8-way directional control. For example, the keys for inputting "1", "2", "3", "4", "6", "7", "8" and "9" would respectively be used for moving NW, N, NE, W, E, SW, S and SE. The key for inputting "5" would be redundant.

The inventor has realised that such an arrangement is not intuitive and generally requires a user to locate a key visually before it is pressed. The inventor has additionally realised that this disadvantage arises from the presence of a redundant key, the use of a large number of keys to achieve the control, and the relatively large separation between, for example, keys for inputting "1" and "9", that is for moving from NW to SE.

It therefore an object of the present invention to provide an improved joystick-like control in a hand portable device using a keypad.

According to one aspect of the present invention there is provided a hand portable device comprising: a user input device comprising a plurality of sensors for tactile actuation by a user including a first sensor and a second sensor adjacent thereto; and control means responsive to the actuation of the first sensor by itself to produce a first control signal, responsive to the actuation of the second sensor by itself to produce a second control signal different from the first control signal, and responsive to the simultaneous actuation of the first and second sensors in combination to produce a third control signal different from the first and second control signals.

According to another aspect of the invention there is provided a method of providing directional control, using the sensors of a keypad of a hand portable device, comprising the steps of: simultaneously sensing an input from each one of a plurality of sensors; associating predetermined control signals with predetermined combinations of simultaneous inputs; detecting simultaneous combinations of inputs to produce a first control signal in response to the actuation of a first sensor by itself, to produce a second control signal in response to actuation of a second sensor by itself, and to produce a third control signal in response to actuation of the first sensor and the second sensor together.

According to a third aspect of the present invention there is provided a user input device for providing 8-way directional control, comprising: a first set of sensors consisting of a first sensor adjacent a second sensor, constituting a first pair of sensors, and a third sensor adjacent the second sensor, constituting a second pair of sensors; and a second set of sensors, adjacent the second set of sensors, consisting of a fourth sensor adjacent a fifth sensor, constituting a third pair of sensors, and a sixth sensor adjacent the fifth sensor, constituting a fourth pair of sensors; wherein user actuation of a respective one of at least four of the six sensors provides for control in a respective one of four different

directions and user actuation of a respective one of the first, second, third and fourth pairs of sensors provides for control in a respective one of the remaining four different directions.

According to a further aspect of the present invention there is provided a method of providing 8-way directional control using a user input device comprising a first set of sensors consisting of a first sensor adjacent a second sensor, constituting a first pair of sensors, and a third sensor adjacent the second sensor, constituting a second pair of sensors and a second set of sensors, adjacent the second set of sensors, consisting of a fourth sensor adjacent a fifth sensor, constituting a third pair of sensors, and a sixth sensor adjacent the fifth sensor, constituting a fourth pair of sensors, comprising the step of: actuating predetermined ones of the sensors to move in any one of a first four orthogonal directions, and actuating predetermined ones of the four pairs of the sensors to move in any one of a second four orthogonal directions, off-set by 45 degrees from the first four orthogonal directions.

Thus embodiments of the present invention provides for the control of the element (for example a cursor or a character in a game) on the screen, for example, by using an existing keypad in a non-standard manner.

For a better understanding of the present invention and to understand how the same may be brought into effect, reference will now be made by way of example only to the accompanying drawings in which:

Fig. 1 is a schematic illustration of a hand portable device;

Fig. 2a illustrates a mobile phone having a conventional 4x3 keypad array for data entry;

Fig. 2b illustrates a mobile phone having a QWERTY keypad for data entry;

Fig. 3 illustrates circuitry which converts the input from six discrete keys into eight distinct signals for controlling directional movement; and

Fig. 4 is a table illustrating how the actuation of keys in a 2x3 array provides eight directional control signals.

Fig. 1 is a schematic illustration of a hand portable device 2 which in this example is a mobile phone. The hand portable device 2 comprises a user interface 10, a processor 20, an input controller 30 and a radio frequency transceiver 40. The processor 20 is bi-directionally connected, to receive an input and provide an output to the user interface 10 and the radio frequency transceiver 40. The user interface 10 comprises a display 12, an audio output 14, an audio input 16 and a keypad 100. The keypad 100 is connected to the input controller 30 which in turn is connected to the processor 20. The keypad 100 comprises a number of function keys 110 and a number of data input keys 120 for inputting numerals and/or alphanumeric characters.

Fig. 2a illustrates a hand portable mobile phone 2 having a twelve key arrangement (three columns and four rows) of keys 120. The data input keys 120 have a sub-set of a plurality of keys 130 arranged as three columns and two rows of six keys. The top left (TL) key 131 is at column one, row one (1, 1). The top centre (T) key 132 is at row one, column two (1, 2). The top right (TR) key 133 is at row one, column three (1, 3). The bottom left (BL) key 134 is at row two, column one (2, 1). The bottom centre (B) key 135 is at row two, column two (2, 2). The bottom right (BR) key 136 is at row two, column three (2, 3).

Fig. 2b illustrates a hand portable mobile phone 2 having a keypad 100 for typing. The data input keys 120 includes a key for each letter in the alphabet (e.g. a QWERTY keyboard). The data input keys are divided into two portions. A first half 120a and a second half 120b are separated by the display 12 and the function keys 110. The data input keys 120 have a sub-set of a plurality of keys 130 arranged as three columns and two rows of six keys. The top left (TL) key 131 is at column one, row one (1, 1). The top centre (T) key

132 is at row one, column two (1, 2). The top right (TR) key 133 is at row one, column three (1, 3). The bottom left (BL) key 134 is at row two, column one (2, 1). The bottom centre (B) key 135 is at row two, column two (2, 2). The bottom right (BR) key 136 is at row two, column three (2, 3).

The keys 131, 132 and 133 are arranged linearly with no intermediate key between them and they form a first set of keys. Although the first set of keys, as illustrated in Figs 2a and 2b, are arranged substantially rectilinearly they may in other embodiments be arranged curvilinearly. The keys 134, 135 and 136 are arranged linearly with no intermediate key between them and they form a second set of keys. Although the second set of keys, as illustrated in Figs 2a and 2b, are arranged substantially rectilinearly they may in other embodiments be arranged curvilinearly. The second set of keys and the first set of keys extend substantially parallel to each other without any intermediate keys between them. The key pairs 131 and 134, 132 and 135 and 133 and 136 are aligned substantially parallel to each other.

In the embodiments illustrated in Figures 2a and 2b the keys 131-136 form an array of 2 rows and 3 columns. A portion of each of the keys 131-133 lies on a first rectilinear axis defining the first row and a portion of each of the keys 134-136 lies on a second rectilinear axis, parallel to the first rectilinear axis, defining the second row. A portion of each of the keys 131 and 134 lies on a third rectilinear axis, perpendicular to the first axis, defining the first column. A portion of each of the keys 132 and 135 lies on a fourth rectilinear axis, parallel to the third axis, defining the second column. A portion of each of the keys 133 and 136 lies on a fifth rectilinear axis, parallel to the third axis, defining the third column.

The distance between the adjacent keys in the first set and the adjacent keys in the second set is from 2 to 6mm. The distance between the first and second sets of keys is between 3 and 8mm. Thus each of the keys 131-136 can be actuated by rolling a thumb or index digit about a fixed position. The key 132 or 135 preferably has a textured surface to allow orientation of the thumb

or index finger on the keypad without using sight.

Fig. 3 illustrates the plurality of keys 130 including the keys 131, 132, 133, 134, 135 and 136. Each key has an underlying switch which in a steady state is open. The actuation of a key by the user closes the switch. The input of each of the switches is connected to a clock signal. The output of the switch corresponding to key 131 provides the first bit of an address to a programmed read-only memory (PROM) 32. The output of the switch corresponding to key 132 provides a second bit of an address to the PROM 32. The output of the switch corresponding to key 133 provides the third bit of an address to PROM 32. The output of the switch corresponding to key 134 provides the fourth bit of an address to PROM 32. The output of the switch corresponding to the key 135 provides the fifth bit of an address to the PROM 32. The output of the switch corresponding to the key 136 provides the sixth bit of an address to the PROM 32. When a switch is in the open, non-actuated position, it provides a logic LOW value as the address bit. When the switch is closed, it provides a logic HIGH value as the address bit with each clock pulse. Consequently, each of the permutations in which the plurality of keys 130 can be actuated either by themselves or in any combination, has a corresponding unique six bit address which is inputted to the PROM 32. The PROM 32 produces a four bit parallel output for each distinct address applied to its input. Thus each possible permutation of actuations of the plurality of keys 130 produces a predefined four bit output 34. The first bit of the four bit output 34 is an enable signal and the remaining three bits is an information signal which represents one of the eight possible directional movements of a joystick which corresponds on a compass to North (moving the joystick forward), South (moving the joystick back), West (moving the joystick to the left), East (moving the joystick to the right), North West (moving the joystick forward and to the left), North East (moving the joystick forward and to the right), South East (moving the joystick back and to the right) and South West (moving the joystick back and to the left).

Fig. 4 illustrates a table which shows the relationship between the actuation of the switches 131 to 136 and the output 34 from the PROM 32. The



table has six columns one for each of the keys 131 to 136. An "X" in a column headed by a particular key indicates the actuation of that key. If one then moves along the row in which that X occurs to columns seven and eight of the table, they indicate the four bit signal 34 including the first enable bit and the three information bits. Column nine of the table indicates which of the eight possible directional movements the output 34 from the PROM 32 indicates to the processor 20.

It will therefore be apparent from the table of Fig. 4 that the actuation of the top centre (T) key 132 by itself corresponds to the movement of a joystick in the North direction. Actuation of the bottom centre (B) key 135 by itself corresponds to the movement of a joystick in the South direction. Actuation of the top left (TL) key 131 by itself or actuation of the bottom left (BL) key 134 by itself or actuation of the top left (TL) key 131 and the bottom left (BL) key 134 together corresponds to the movement of a joystick in the West direction. Actuation of the top right (TR) key 133 by itself or the bottom right (BR) key 136 by itself or actuation of the top right (TR) key 133 and the bottom right (BR) key 136 together corresponds to the movement of a joystick in the East direction. Actuation of the top left (TL) key 131 and the top centre (T) key 132 together corresponds to movement of a joystick in the North West direction. Actuation of the top centre (T) key 132 and the top right (TR) key 133 together corresponds to the movement of a joystick in the North East direction. Actuation of the bottom left (BL) key 134 and the bottom centre (B) key 135 together corresponds to the movement of a joystick in the South West direction. Actuation of the bottom centre (B) key 135 and the bottom right (BR) key 136 together corresponds to movement of a joystick in the North East direction. All other input permutations of the plurality of keys 130 results in the first bit of the output of the PROM 32 being logic LOW which corresponds to no movement of a joystick.

According to one embodiment (shown in Fig. 4) the actuation of the top left (TL) key 131, the top centre (T) key 132 and the top right (TR) key 133 together is interpreted as actuation of only the top centre (T) key 132. Likewise

the simultaneous actuation of the bottom left (BL) key 134, the bottom centre (B) key 135 and the bottom right (BR) key 136 is interpreted as the actuation of only the bottom centre (B) key 135.

When the first bit of the output of the PROM 32 is HIGH, the processor interprets the three information bits which constitute the remainder of the output of the PROM 32. Thus the 2x3 array of keys 131 to 136 provides an eight way input which emulates a joystick.

It is preferable for the actuation of one or more of the plurality of keys 130 to occur by the pivoting of an index finger or thumb between the top centre (T) key 132 and the bottom centre (B) key 135. A forward rocking motion of the digit therefore actuates the top centre (T) key 132 and a backward rocking motion of the digit actuates the bottom centre (B) key 135. A leftwards rocking motion of the digit actuates either one or both of the top left (TL) key 131 and the bottom left (BL) key 134 and a rightwards rocking motion of the digit actuates either one or both of the top right (TR) key 133 and the bottom right (BR) key 136. A rocking motion of the digit in the North Westerly direction actuates both the top left (TL) key 131 and the top centre (T) key 132. A rocking of the digit in the North Easterly direction actuates both the top centre (T) key 132 and the top right (TR) key 133. A rocking motion of the digit in the South Easterly direction actuates both the bottom right (BR) key 136 and the bottom centre (B) key 135. A rocking motion of the digit in the South Westerly direction actuates both the bottom left (BL) key 134 and the bottom centre (B) key 135. Thus the plurality of keys 130 provides for eight way control using one digit, which is pivoted about a stationary point. To enable the eight way directional control with the pivoting of a single digit it is preferable for the plurality of keys 130 to lie within a rectangle having a length of approximately 20 mm and a height of approximately 15 mm. Thus the 8-way control provided by the keypad is highly intuitive and does not requires a digit to be lifted from the keypad and re-oriented to simultaneously actuate two keys. The keypad can therefore be easily used for 8-way control without looking at it.

It should be made apparent that the plurality of keys 130 are not keys which are dedicated to the aforementioned joystick-like control. They are keys which in a data entry mode indicate a numeral or letter for input but which in a cursor control or gaming mode provide for eight way directional control. In such a data entry mode the simultaneous depression of two keys is ambiguous and processor 20 is programmed not to interpret such a simultaneous depression as a special input.

The plurality of key 130 may be used to control a cursor on the display 12 or move an element within a game displayed from a third person perspective. Alternatively, a game may be displayed from a first person perspective of the game character in which case the plurality of keys change the perspective by 'moving' the character.

Although the plurality of keys 130 are implemented as switches in Fig 3, the invention is not limited to this implementation as any device (sensor) which senses touch may be used.

It is envisaged that the normal cover of a mobile phone having twelve openings for each of the twelve data input keys could be replaced by a cover in which keys "1" to "6" or the keys "4" to "#" are replaced by a single key or joystick device. The sensor or switches associated with each of the keys is unaffected. The underside of the single key is arranged so that it actuates a single sensor or pairs of sensors to provide 8-way directional control in the manner previously described.

Although a PROM 32 was used in Fig. 3 to translate the possible permutations of actuations of the plurality of keys into eight control signals, other means exist for carrying out the same purpose. For example, discrete logical elements, programmable logic devices or a programmed microcontroller could be used. In fact, the processor 20, itself, could carry out the process using software.

Although in the foregoing the keys 131-136 are in a 2 row by three column arrangement, they could of course be re-oriented in a 3 row by two column arrangement.

Whilst endeavouring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance it should be understood that the Applicant claims protection in respect of any patentable feature or combination of features hereinbefore referred to and/or shown in the drawings whether or not particular emphasis has been placed thereon.

CLAIMS

1. A hand portable device comprising:  
a user input device comprising a plurality of sensors for tactile actuation by a user including a first sensor and a second sensor adjacent thereto; and  
control means responsive to the actuation of the first sensor by itself to produce a first control signal, responsive to the actuation of the second sensor by itself to produce a second control signal different from the first control signal, and responsive to the simultaneous actuation of the first and second sensors in combination to produce a third control signal different from the first and second control signals.
2. A hand portable device as claimed in claim 1, wherein the plurality of sensors comprises a first set of sensors consisting of a first sensor adjacent a second sensor, constituting a first pair of sensors, and a third sensor adjacent the second sensor, constituting a second pair of sensors; and a second set of sensors consisting of a fourth sensor adjacent a fifth sensor, constituting a third pair of sensors, and a sixth sensor adjacent the fifth sensor, constituting a fourth pair of sensors.
3. A hand portable device as claimed in claim 2 wherein the pairs of sensors are located and arranged to be simultaneously actuated by a user using one digit.
4. A hand portable device as claimed in claim 2 or 3 wherein the first set of sensors is adjacent the second set of sensors.
5. A hand portable device as claimed in 2, 3 or 4, wherein the control means is responsive to user actuation of a respective one of at least four of the six sensors to provide a respective one of four different control signals and is responsive to user actuation of a respective one of the first, second, third and fourth pairs of sensors to provides for a respective one of an additional four different control signals.

6. A hand portable device as claimed in claim 2, 3, 4 or 5, wherein the control means produces:

- (a) a first control signal in response to the actuation of the second sensor;
- (b) a second control signal in response to the actuation of the first sensor;
- (c) a third control signal in response to actuation of both the first and second sensors simultaneously;
- (d) a fourth control signal in response to the actuation of the third sensor;
- (e) a fifth control signal in response to the actuation of both the second and third sensors simultaneously;
- (f) a sixth control signal in response to the actuation of the fifth sensor;
- (g) a seventh control signal in response to the actuation of both the fifth and sixth sensors simultaneously; and
- (h) an eighth control signal in response to the actuation of both the fourth and fifth sensors simultaneously.

7. A hand portable device as claimed in claim 6 wherein the control means in response to the actuation of only the fourth sensor produces the second control signal and in response to actuation of only the sixth sensor produces the fourth control signal.

8. A hand portable device as claimed in any preceding claim wherein the control means comprises detection means for detecting the simultaneous actuation of keys.

9. A hand portable device as claimed in any preceding claim wherein the plurality of sensors is a 2x3 or 3x2 array of sensors.

10. A hand portable device as claimed in any preceding claim when dependent upon claim 2 wherein the user input device is a keypad having first,

second, third, fourth, fifth and sixth keys which respectively actuate the first, second, third, fourth, fifth and sixth sensors whereby the first, second, third and fourth pairs of sensors have corresponding first, second, third and fourth pairs of keys.

11. A hand portable device as claimed in claim 10 wherein each pair of keys are located and arranged to be simultaneously actuated by a user using one digit.

12. A hand portable device as claimed in claim 10 or 11 wherein the pairs of keys are located and arranged to be actuated by a user rolling or pivoting one digit.

13. A hand portable device as claimed in any one of claims 10 to 12, wherein the first, second and third keys are arranged curvilinearly.

14. A hand portable device as claimed in any one of claims 10 to 12, wherein the first, second and third keys are arranged rectilinearly.

15. A hand portable device as claimed in any one of claims 10 to 14 wherein the fourth, fifth and sixth keys are arranged substantially parallel to the first, second and third keys.

16. A hand portable device as claimed in any one of claims 10 to 15, wherein the first, second, third, fourth, fifth and sixth keys form an array.

17. A hand portable device as claimed in any preceding claim wherein the first, second, third, fourth, fifth and sixth keys occupy an area not significantly exceeding 20 mm by 15 mm.

18. A hand portable device as claimed in any one of claims 10 to 17 wherein the keypad comprises a 4x3 array of mobile telephone keys.

19. A hand portable device as claimed in any one of claims 10 to 17 wherein the keypad is a typist's keypad.

20. A hand portable device as claimed in any one of claims 10 to 19 having a data entry mode where the keypad including the plurality of keys are used to enter data wherein in said data entry mode the control means is responsive to the actuation of the first key and second key separately but not together to produce different control signals.

21. A hand portable device as claimed in any preceding claim further comprising a display for displaying an image including an element moving in the display, wherein the first control signal causes the element to move in a first direction, the second control signal causes the element to move in a second direction and the third control signal causes the element to move in a third direction intermediate of the first and second directions.

22. A hand portable device as claimed in any one of claims 1 to 20 further comprising a display for displaying an image having a perspective dependent upon a notional viewing position, wherein the first control signal causes the notional viewing position to move in a first direction, the second control signal causes the notional viewing position to move in a second direction and the third control signal causes the notional viewing position to move in a third direction intermediate of the first and second directions.

23. A method of providing directional control, using the sensors of a keypad of a hand portable device, comprising the steps of:

- simultaneously sensing an input from each one of a plurality of sensors;
- associating predetermined control signals with predetermined combinations of simultaneous inputs;

- detecting simultaneous combinations of inputs to produce a first control signal in response to the actuation of a first sensor by itself, to produce a second control signal in response to actuation of a second sensor by itself, and to produce a third control signal in response to actuation of the first sensor and



the second sensor together.

24. A user input device for providing 8-way directional control, comprising a first set of sensors consisting of a first sensor adjacent a second sensor, constituting a first pair of sensors, and a third sensor adjacent the second sensor, constituting a second pair of sensors; and a second set of sensors, adjacent the second set of sensors, consisting of a fourth sensor adjacent a fifth sensor, constituting a third pair of sensors, and a sixth sensor adjacent the fifth sensor, constituting a fourth pair of sensors; wherein

user actuation of a respective one of at least four of the six sensors provides for control in a respective one of four different directions and

user actuation of a respective one of the first, second, third and fourth pairs of sensors provides for control in a respective one of the remaining four different directions.

25. A user input device as claimed in claim 24, wherein the pairs of sensors are located and arranged to be simultaneously actuated by a user using one digit.

26. A user input device as claimed in claim 24 or 25, wherein the plurality of sensors is a 2x3 or 3x2 array of sensors.

27. A user input device as claimed in claim 24, 25 or 26, comprising a keypad having first, second, third, fourth, fifth and sixth keys which respectively actuate the first, second, third, fourth, fifth and sixth sensors whereby the first, second, third and fourth pairs of sensors have corresponding first, second, third and fourth pairs of keys.

28. A user input device as claimed in claim 27 wherein each pair of keys are located and arranged to be simultaneously actuated by a user using one digit.

29. A user input device as claimed in claim 27 or 28 wherein the pairs of

keys are located and arranged to be actuated by a user rolling or pivoting one digit.

30. A user input device as claimed hand portable device as claimed in any one of claims 27 to 29, wherein the first, second and third keys are arranged curvilinearly.

31. A user input device as claimed in any one of claims 27 to 29, wherein the first, second and third keys are arranged rectilinearly.

32. A user input device as claimed in any one of claims 27 to 31 wherein the fourth, fifth and sixth keys are arranged substantially parallel to the first, second and third keys.

33. A user input device as claimed in any one of claims 27 to 29, wherein the first, second, third, fourth, fifth and sixth keys form an array.

34. A user input device as claimed in any one of claims 27 to 33, wherein the first, second, third, fourth, fifth and sixth keys occupy an area not significantly exceeding 20 mm by 15 mm.

35. A user input device as claimed in any one of claims 27 to 34 wherein the keypad comprises a 4x3 array of mobile telephone keys.

36. A user input device as claimed in any one of claims 27 to 34, wherein the keypad is a typist's keypad.

37. A hand portable device comprising a user input device as claimed in any one of claims 24 to 36, and control means, wherein the control means produces:

- (a) a first control signal in response to the actuation of the second sensor;
- (b) a second control signal in response to the actuation of the first sensor;

- (c) a third control signal in response to actuation of both the first and second sensors simultaneously;
- (d) a fourth control signal in response to the actuation of the third sensor;
- (e) a fifth control signal in response to the actuation of both the second and third sensors simultaneously;
- (f) a sixth control signal in response to the actuation of the fifth sensor;
- (g) a seventh control signal in response to the actuation of both the fifth and sixth sensors simultaneously; and
- (h) an eighth control signal in response to the actuation of both the fourth and fifth sensors simultaneously.

38. A hand portable device as claimed in claim 37 wherein the control means in response to the actuation of only the fourth sensor produces the second control signal and in response to actuation of only the sixth sensor produces the fourth control signal.

39. A hand portable device as claimed in claim 37 or 38, wherein the control means comprises detection means for detecting the simultaneous actuation of keys.

40. A hand portable device as claimed in any one of claims 37 to 39 having a data entry mode where the keypad including the plurality of keys are used to enter data wherein in said data entry mode the control means is responsive to the actuation of the first key and second key separately but not together to produce different control signals.

41. A hand portable device as claimed in any one of claims 37 to 40 further comprising a display for displaying an image including an element moving in the display, wherein the first control signal causes the element to move in a first direction, the second control signal causes the element to move in a second direction and the third control signal causes the element to move in a third



direction intermediate of the first and second directions.



42. A hand portable device as claimed in any one of claims 37 to 40. further comprising a display for displaying an image having a perspective dependent upon a notional viewing position, wherein the first control signal causes the notional viewing position to move in a first direction, the second control signal causes the notional viewing position to move in a second direction and the third control signal causes the notional viewing position to move in a third direction intermediate of the first and second directions.

43. A method of providing 8-way directional control using a user input device comprising a first set of sensors consisting of a first sensor adjacent a second sensor, constituting a first pair of sensors, and a third sensor adjacent the second sensor, constituting a second pair of sensors and a second set of sensors, adjacent the second set of sensors, consisting of a fourth sensor adjacent a fifth sensor, constituting a third pair of sensors, and a sixth sensor adjacent the fifth sensor, constituting a fourth pair of sensors, comprising the steps of:

actuating predetermined ones of the sensors to move in any one of a first four orthogonal directions, and

actuating predetermined ones of the four pairs of the sensors to move in any one of a second four orthogonal directions, off-set by 45 degrees from the first four orthogonal directions.

**FIG. 1****FIG. 3**



3/3

130						34		Movement
131	132	133	134	135	136	EN	INFO.	Direction
TL	T	TR	BL	B	BR			
	X					1	100	↑
				X		1	001	↓
X						1	010	←
			X			1	010	←
X			X			1	010	←
		X				1	101	→
					X	1	101	→
		X			X	1	101	→
X	X					1	110	↖
	X	X				1	011	↗
			X	X		1	111	↘
				X	X	1	000	↗
X	X	X				1	100	↑
			X	X	X	1	001	↓
<u>- Other Permutations -</u>						0		
						0		
						0		
						0		
						0		
						0		

***FLA***

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 02/01878

A. CLASSIFICATION OF SUBJECT MATTER  
 IPC 7 G06F3/023 H04M1/247

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EP0-Internal, PAJ, IBM-TDB

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	ANONYMOUS: "Keyboard Cursor Control Layout" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 26, no. 4, 1 September 1983 (1983-09-01), pages 1967-1968, XP002226449 New York, US the whole document	1-43
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 373 (P-1400), 11 August 1992 (1992-08-11) & JP 04 118715 A (NIHON AI ENU ESU:KK), 20 April 1992 (1992-04-20) abstract	1,21-23
A	---	41,42
	---	---

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

13 January 2003

Date of mailing of the international search report

23/01/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Bailas, A



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/01878

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 367 316 A (IKEZAKI MASAO) 22 November 1994 (1994-11-22) column 8, line 60 -column 9, line 11 -----	1,23
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 04, 31 August 2000 (2000-08-31) -& JP 2000 032110 A (HITACHI LTD), 28 January 2000 (2000-01-28) abstract; figures 2,3,13 -----	1,20,21, 23,24, 35,40,43

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP02/01878

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 04118715	A	20-04-1992	NONE	
US 5367316	A	22-11-1994	JP JP	2636624 B2 5318040 A
				30-07-1997 03-12-1993
JP 2000032110	A	28-01-2000	NONE	